



## DFS MEASUREMENT REPORT

### EN 302 502 V1.2.1

---

**Applicant:** Compex Systems Pte Ltd

**Address:** 135, Joo Seng Road, #08-01 Singapore 368363

**Product:** 802.11ac Dual Band Module

**Model No.:** WLE600VX

**Brand Name:** COMPEX

**Standards:** EN302502 V1.2.1 (2007-08) Clause 4.6

**Type of Device:** ☒ Master Device  
☐ Client Device without radar detection  
☐ Client Device with radar detection

**Result:** Complies

**Test Date:** Mar. 16 ~ Jun. 15, 2015

Reviewed By : Robin Wu  
( Robin Wu )

Approved By : Marlin Chen  
( Marlin Chen )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

| Report No.   | Version | Description    | Issue Date |
|--------------|---------|----------------|------------|
| 1503RSU02909 | Rev. 01 | Initial report | 06-15-2015 |
|              |         |                |            |

## CONTENTS

| Description   | Page      |
|---|-----------|
| <b>1. General Information .....</b>   | <b>5</b>  |
| 1.1. Applicant.....   | 5         |
| 1.2. Manufacturer .....   | 5         |
| 1.3. Testing Facility .....   | 5         |
| 1.4. Feature of Product .....   | 6         |
| 1.5. Product Specification Subjective to this Report.....                               | 6         |
| 1.6. Operation Frequency / Channel List .....   | 6         |
| 1.7. Description of Available Antennas.....   | 7         |
| 1.8. Test Channel / Test Mode .....   | 7         |
| 1.9. Standards Applicable for Testing .....   | 7         |
| <b>2. DFS Requirements and Radar Test Waveforms .....</b>                               | <b>8</b>  |
| 2.1. Applicability .....  | 8         |
| 2.2. DFS Detection Threshold Values .....   | 8         |
| 2.3. Radar Wave Parameters .....  | 8         |
| 2.4. Conducted Test Setup .....   | 11        |
| <b>3. Test Equipment Calibration Date .....</b>   | <b>12</b> |
| <b>4. Test Summary.....</b>   | <b>13</b> |
| <b>5. Test Result.....</b>  | <b>14</b> |
| 5.1. Radar Waveform Calibration.....  | 14        |
| 5.2. Initial Channel Availability Check Time Measurement .....                          | 19        |
| 5.2.1 Test Limit .....  | 19        |
| 5.2.2 Test Procedure .....  | 19        |
| 5.2.3 Test Result.....  | 19        |
| 5.3. Radar Burst at the Beginning of the Channel Availability Check Time Measurement .. | 20        |
| 5.3.1 Test Limit .....  | 20        |
| 5.3.2 Test Procedure .....  | 20        |
| 5.3.3 Test Result.....  | 21        |
| 5.4. Radar Burst at the End of the Channel Availability Check Time Measurement.....     | 22        |
| 5.4.1 Test Limit .....  | 22        |
| 5.4.2 Test Procedure .....  | 22        |
| 5.4.3 Test Result.....  | 23        |
| 5.5. Interference Detection Threshold (during the Channel Availability Check) .....     | 24        |
| 5.5.1 Test Limit .....  | 24        |
| 5.5.2 Test Procedure .....  | 24        |
| 5.5.3 Test Result.....  | 25        |
| 5.6. In-Service Monitoring Measurement .....  | 26        |

---

|  |    |
|--|----|
| 5.6.1 Test Limit .....                               | 26 |
| 5.6.2 Test Procedure Used .....                      | 26 |
| 5.6.3 Test Result.....                               | 27 |
| 5.7. Channel Shutdown and Non-Occupancy Period ..... | 28 |
| 5.7.1 Test Limit .....                               | 28 |
| 5.7.2 Test Procedure Used .....                      | 28 |
| 5.7.3 Test Result.....                               | 29 |

## 1. General Information

### 1.1. Applicant

Compex Systems Pte Ltd  
135 Joo Seng Road, #08-01 Singapore 368363

### 1.2. Manufacturer

Compex Systems Pte Ltd  
135 Joo Seng Road, #08-01 Singapore 368363

### 1.3. Testing Facility

#### Test Site

MRT Technology (Suzhou) Co., Ltd

#### Test Site Location

D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China

#### Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China

- MRT facility is a FCC registered (MRT Reg. No. 809388) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



#### 1.4. Feature of Product

|                     |                           |
|---------------------|---------------------------|
| Product Name        | 802.11ac Dual Band Module |
| Model No.           | WLE600VX                  |
| Brand Name          | COMPEX                    |
| Wi-Fi Specification | 802.11a/b/g/n/ac          |

#### 1.5. Product Specification Subjective to this Report

|                    |   |
|--------------------|---|
| Frequency Range    | 802.11a/n-HT20/ac-VHT20: 5745 ~ 5825MHz   |
| Channel Number     | 802.11a/n-HT20/ac-VHT20: 5  |
| Type of Modulation | 802.11a/n/ac: OFDM  |
| Data Rate          | 802.11a: 6/9/12/18/24/36/48/54Mbps<br>802.11n: up to 300Mbps<br>802.11ac: up to 866.6Mbps |

Note: For other features of this EUT, test report will be issued separately.

#### 1.6. Operation Frequency / Channel List

802.11a/n-HT20/ac-VHT20

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 149     | 5745 MHz  | 153     | 5765 MHz  | 157     | 5785 MHz  |
| 161     | 5805 MHz  | 165     | 5825 MHz  | N/A     | N/A       |

### 1.7. Description of Available Antennas

| Antenna No. | Manufacturer                          | Tx Paths | Max Directional Gain (dBi) |
|-------------|---------------------------------------|----------|----------------------------|
| Antenna 1#  | Kunshan Wavelink Electronic Co., Ltd. | 2        | 2.4GHz: 2.0, 5GHz: 2.0     |
| Antenna 2#  | TAOGLAS Inc                           | 2        | 2.4GHz: 4.5, 5GHz: 6.7     |
| Antenna 3#  | Compex Systems Pte Ltd                | 2        | 2.4GHz: 5.0, 5GHz: 5.0     |
| Antenna 4#  | Compex Systems Pte Ltd                | 2        | 2.4GHz: 5.0, 5GHz: 5.0     |
| Antenna 5#  | Smart Ant Inc                         | 2        | 5GHz: 7.0                  |
| Antenna 6#  | Kenbotong Communication LTD           | 2        | 5GHz: 10.0                 |

Note 1: The frequency bands (5150~5350MHz & 5470~5725MHz) support the max antenna gain 7dBi and another frequency band (5725~5850MHz) supports the max antenna gain 10dBi.

Note 2: We selected the antenna 5# for all radiated emission testing.

### 1.8. Test Channel / Test Mode

| Test Mode    | Test Channel |         |
|--------------|--------------|---------|
| 802.11n-HT20 | 149          | 5745MHz |

### 1.9. Standards Applicable for Testing

The EUT complies with the requirements of EN 302502 V1.2.1 clause 4.6.

## 2. DFS Requirements and Radar Test Waveforms

### 2.1. Applicability

**Table 2-1: DFS requirement values**

| Parameter                         | Value    |
|-----------------------------------|----------|
| Channel Availability Check Time   | 60 s     |
| Channel Move Time                 | 10 s     |
| Channel Closing Transmission Time | 260 ms   |
| Non-Occupancy Period              | 30 min   |
| Channel Revalidation Period       | 24 hours |

### 2.2. DFS Detection Threshold Values

**Table D 2-2: Interference threshold values**

| EIRP Spectral Density dBm/MHz  | Value (see notes 1 and 2) |
|--|---------------------------|
| 23   | -69 dBm                   |
| <p>NOTE 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.</p> <p>NOTE 2: For FWA devices employing lower EIRP spectral density and a receive antenna gain G (dBi) the threshold follows the following relationships.</p> <p>DFS Detection Threshold (dBm) = -69 + 23 -EIRP Spectral Density (dBm/MHz) + G (dBi). See table D.4 for example calculations.</p> |                           |

### 2.3. Radar Wave Parameters

**Table 2-3: DFS Test Signals simulating fixed frequency radars**

| Radar test signal (see notes 2)   | Pulse width W [μs](see note 5)<br>Choose one value | Pulse repetition frequency PRF (PPS)<br>Choose one value | Pulses per burst (see notes 1 and 3) | Detection probability with 30% channel load (see note 4) |
|---|--|--|--------------------------------------|--|
| 1-Fixed   | 1  | 750  | 15                                   | Pd > 60 %  |
| 2-Variable  | 1,2,5  | 200,300,500,800,1000                                     | 10                                   | Pd > 60 %  |
| 3-Variable  | 10,15  | 200,300,500,800,1000                                     | 15                                   | Pd > 60 %  |
| 4-Variable  | 1,2,5,10,15  | 1200,1500,1600   | 15                                   | Pd > 60 %  |
| 5-Variable  | 1,2,5,10,15  | 2300,3000,3500,4000                                      | 25                                   | Pd > 60 %  |
| 6-Variable modulated (see note 6)   | 20,30  | 2000,3000,4000   | 20                                   | Pd > 60 %  |
| NOTE 1: This represents the number of pulses seen at the device per radar scan: |  |  |                                      |  |



$N = \{ \text{antenna beamwidth (deg)} \} \times \{ \text{pulse repetition rate (pps)} \} / \{ \text{scan rate (deg/s)} \}$ .

NOTE 2: The test signals above only contain a single burst of pulses. See figure 2-1.

NOTE 3: The number of pulses per burst given in this table simulate real radar systems and take into account the effects of pulse repetition rate and pulse width on the detection probability for a single burst.

NOTE 4:  $P_d$  gives the probability of detection per simulated radar burst and represents a minimum level of detection performance under defined conditions - see clause 5.1.2.2.

Therefore  $P_d$  does not represent the overall detection probability for any particular radar under real life conditions. In general 5 sequential bursts are needed to achieve a real life detection rate of better than 99 % for any radar that falls within the scope of the above table.

NOTE 5: The pulse width used in these tests is assumed to be representative of real radar systems with different pulse widths and different modulations. The pulse width is assumed to have an accuracy of  $\pm 5\%$ .

NOTE 6: The modulation to be used for the radar test signal 6 is a chirp modulation with a  $\pm 2,5$  MHz frequency deviation which is illustrated below.





Figure 1: General structure of a single burst DFS test transmission

**Table 2-4: DFS Test Signals simulating Frequency Hopping radars**

| Radar test signal | Pulse width W[μs] | Pulse repetition Frequency PRF [pps] | Pulses Per burst | Burst Length [ms] | Bursts per Trial (see note 4) | Pulse modulation (see note 1) | Detection Probability Pd with 30 % channel load (see note 2) |
|-------------------|-------------------|--------------------------------------|------------------|-------------------|-------------------------------|-------------------------------|--|
| 1                 | 1                 | 3000                                 | 9                | 3                 | 8                             | none                          | see note 3   |
| 2                 | 20                | 4500                                 | 9                | 2                 | 2                             | chirp                         | see note 3   |

NOTE 1: Modulation used is defined in note 6, Table 2-3.

NOTE 2: Pd gives the probability of detection per simulated radar test signal and represents a minimum level of detection performance under defined conditions - see clause 5.1.2.2.

The test is performed using a minimum of 30 trials per test signal. The probability of detection is calculated by

$$Pd = \frac{\text{TotalSetDetections}}{\text{TotalSetTrials}} \times 100.$$

NOTE 3: For ChS = 10 MHz, Pd > 60 %; for ChS = 20 MHz, Pd > 70 %.

NOTE 4: For each of the trials, the burst interval will increase from 1,25 ms to 37,5 ms in Steps of 1,25 ms for radar signal 1 and from 5 ms to 150 ms in Steps of 5 ms for radar signal 2.

**Table 2-5: Example Interference Threshold values**


| Maximum EIRP (dBm) | Channel Width (MHz) ChS | EIRP Spectral Density (dBm/MHz) | Interference Threshold (dBm) | Antenna Gain (dBi) | DFS Detection Threshold (dBm) |
|--------------------|-------------------------|---------------------------------|------------------------------|--------------------|-------------------------------|
| 29.87              | 20                      | 20.18                           | -69                          | 10                 | -56.18                        |

Note: We use the worst interference threshold -69dBm for DFS testing.


## 2.4. Conducted Test Setup

The following equipment setup was used to calibrate the conducted radar waveform. A spectrum analyzer was used to establish the test signal level for each radar type. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was utilized. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 1 MHz and 3 MHz.

The signal generator amplitude was set so that the power level measured at the spectrum analyzer was -55dBm due to the interference threshold level is not required



**DFS Test Set-up Photo for Master Device - Set-up A**



### 3. Test Equipment Calibration Date

Dynamic Frequency Selection (DFS)

| Instrument                  | Manufacturer | Type No. | Cali. Interval | Cali. Due Date |
|-----------------------------|--------------|----------|----------------|----------------|
| Spectrum Analyzer           | Agilent      | N9020A   | 1 year         | 2016/04/23     |
| ESG Vector Signal Generator | Agilent      | E4438C   | 1 year         | 2015/12/09     |

| Software       | Manufacturer | Function                         |
|----------------|--------------|----------------------------------|
| Pulse Building | Agilent      | Radar Signal Generation Software |
| DFS Tool       | Agilent      | DFS Test Software                |

#### 4. Test Summary


| Parameter   | Limit                   | Test Result | Reference   |
|---|-------------------------|-------------|-------------|
| Radar Waveform Calibration  | Refer Table 2-3 and 2-4 | Pass        | Section 5.1 |
| Initial Channel Availability Check Time                                       | Refer Table 2-1         | Pass        | Section 5.2 |
| Radar Burst at the Beginning of the Channel Availability Check Time           | Refer Table 2-1         | Pass        | Section 5.3 |
| Radar Burst at the End of the Channel Availability Check Time                 | Refer Table 2-1         | Pass        | Section 5.4 |
| Interference Detection Threshold  | Refer Table 2-2         | Pass        | Section 5.5 |
| In-Service Monitoring   | Refer Table 2-1         | Pass        | Section 5.6 |
| Channel Move Time, Channel Closing Transmission Time and Non-Occupancy Period | Refer Table 2-1         | Pass        | Section 5.7 |

## 5. Test Result


### 5.1. Radar Waveform Calibration

The following equipment setup was used to calibrate the conducted radar waveform. A spectrum analyzer was used to establish the test signal level for each radar type. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was utilized. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 1 MHz and 3 MHz.


**Conducted Calibration Setup**




### Radar Type 1 Calibration Plot




### Radar Type 2 Calibration Plot



### Radar Type 3 Calibration Plot




### Radar Type 4 Calibration Plot







### Radar Type 5 Calibration Plot




### Radar Type 6 Calibration Plot



### Hopping Radar Type 1 Calibration Plot



### Hopping Radar Type 2 Calibration Plot



## 5.2. Initial Channel Availability Check Time Measurement

### 5.2.1 Test Limit

The Channel Availability Check shall be performed during a continuous period in time (Channel Availability Check Time) which shall not be less than the value defined in table 2-1.


### 5.2.2 Test Procedure

1. The devices will be powered on and be instructed to operate on the appropriate channel which falls within the frequency range 5725-5850MHz. At the same time the EUT is powered on, the spectrum analyzer will be set to zero span mode with a 1 MHz RBW and 3 MHz VBW on the Channel occupied by the radar (Ch<sub>r</sub>). The spectrum analyzer's sweep will be started at the same time power is applied to the master device.
2. The EUT should not transmit any beacon or data transmissions until at least 1 minute after the completion of the power-on cycle.
3. Confirm that the EUT initiates transmission on the channel. Measurement system showing its nominal noise floor is marker1.

### 5.2.3 Test Result

The EUT does not transmit any beacon or data transmissions until at least 1 minute after the completion of the power-on cycle (89.30 sec). Initial beacons/data transmissions are indicated by marker 1 (29.30 sec).

Initial Channel Availability Check Time for 802.11n-HT20(5745MHz)



### **5.3. Radar Burst at the Beginning of the Channel Availability Check Time Measurement**

#### **5.3.1 Test Limit**

The Channel Availability Check shall be performed during a continuous period in time (Channel Availability Check Time) which shall not be less than the value defined in table 2-1.

During the Channel Availability Check, the device shall be capable of detecting any of the radar signals that fall within the range given by tables 2-3 and 2-4 with a level above the Interference Detection Threshold defined in table 2-2.

The detection probability for a given radar signal shall be greater than the value defined in tables 2-3 and 2-4.

The Channel Revalidation Period for Available Channels remains valid for a maximum period as defined in table 2-1.

#### **5.3.2 Test Procedure**

a) The signal generator and UUT are connected using the test set-up described in clause 2.4 and the power of the UUT is switched off.


b) The UUT is powered on at  $T_0$ .  $T_1$  denotes the instant when the UUT has completed its power-up sequence ( $T_{\text{power\_up}}$ ) and is ready to start the radar detection. The Channel Availability Check is expected to commence on  $Ch_r$  at instant  $T_1$  and is expected to end no sooner than  $T_1 + T_{\text{ch\_avail\_check}}$  unless a radar is detected sooner.

Note: Additional verification may be needed to define  $T_1$  in case it is not exactly known or indicated by the UUT.

c) A single radar burst is generated on  $Ch_r$  using the radar test signal #1 defined in table 2-3 at a level of up to 10 dB above the level defined in table 2-2. This single-burst radar test signal shall commence within 2 s after time  $T_1$ .


d) It shall be recorded if the radar test signal was detected.

e) A timing trace or description of the observed timing and behaviour of the UUT shall be recorded.



### 5.3.3 Test Result

Radar Burst at the Beginning of the Channel Availability Check Time for 802.11n-HT20 (5745MHz)



## 5.4. Radar Burst at the End of the Channel Availability Check Time Measurement

### 5.4.1 Test Limit

The Channel Availability Check shall be performed during a continuous period in time (Channel Availability Check Time) which shall not be less than the value defined in table 2-1.


During the Channel Availability Check, the device shall be capable of detecting any of the radar signals that fall within the range given by tables 2-3 and 2-4 with a level above the Interference Detection Threshold defined in table 2-2.

The detection probability for a given radar signal shall be greater than the value defined in tables 2-3 and 2-4.

The Channel Revalidation Period for Available Channels remains valid for a maximum period as defined in table 2-1.


### 5.4.2 Test Procedure

- a) The signal generator and UUT are connected using the test set-up described in clause 2.4 and the power of the UUT is switched off.
- b) The UUT is powered up at  $T_0$ .  $T_1$  denotes the instant when the UUT has completed its power-up sequence ( $T_{\text{power\_up}}$ ) and is ready to start the radar detection. The Channel Availability Check is expected to commence on  $\text{Ch}_r$  at instant  $T_1$  and is expected to end no sooner than  $T_1 + T_{\text{ch\_avail\_check}}$  unless a radar is detected sooner.
- c) A single radar burst is generated on  $\text{Ch}_r$  using the radar test signal #1 defined in table 2-3 at a level of up to 10 dB above the level defined in table 2-2. This single-burst radar test signal shall commence towards the end of the minimum required Channel Availability Check Time but not before time  $T_1 + T_{\text{ch\_avail\_check}} - 2 \text{ s}$ .
- d) It shall be recorded if the radar test signal was detected.
- e) A timing trace or description of the observed timing and behaviour of the UUT shall be recorded.



### 5.4.3 Test Result

Radar Burst at the End of the Channel Availability Check Time for 802.11n-HT20 (5745MHz)



## **5.5. Interference Detection Threshold (during the Channel Availability Check)**

### **5.5.1 Test Limit**


The minimum required detection probability associated with a given radar test signal is defined in table 2-4.

### **5.5.2 Test Procedure**

The different Steps below define the procedure to verify the Interference Detection Threshold during the Channel Availability Check Time This is illustrated in figure below.

- a) the signal generator and UUT are connected using the test set up described in clause 2.4 and the power of the UUT is switched off.
- b) The UUT is powered on at T0. T1 denotes the instant when the UUT has completed its power-up sequence ( $T_{\text{power\_up}}$ ) and is ready to start the radar detection. The Channel Availability Check on  $\text{Ch}_r$  is expected to commence at instant T1 and is expected to end no sooner than  $T1 + T_{\text{ch\_avail\_check}}$  unless a radar is detected sooner.
- c) a radar signal is generated on  $\text{Ch}_r$  using radar test signal #1 defined in table 2-3 at a level defined in table 2-2. This radar test signal shall commence at approximately 10 seconds after T1.
- d) It shall be recorded if the radar test signal was detected.
- e) the Steps c) to d) shall be repeated at least 20 times in the case of test signals simulating fixed frequency radars or 30 times in the case of test signals simulating frequency hopping radars in order to determine the detection probability for the selected radar test signal. The detection probability shall be compared with the limit specified in table 2-3 or 2-4 as appropriate.
- f) the Steps c) to e) shall be repeated for each of the radar test signals defined in table 2-3 and for each of the radar test signals defined in table D 3.2 where the single-burst radar signal is replaced by the multi-burst sequence defined in clause 5.3.6.1.1.





### 5.5.3 Test Result

802.11n-HT20 channel 149 5745MHz

| Radar Wave Type | Detection Threshold | Trail Number | Detection Result | Limit | Note |
|-----------------|---------------------|--------------|------------------|-------|------|
| Type 1          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 2          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 3          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 4          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 5          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 6          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Hopping Type 1  | -69dBm              | 20           | 100%             | 60%   | Pass |
| Hopping Type 2  | -69dBm              | 20           | 100%             | 60%   | Pass |

## **5.6. In-Service Monitoring Measurement**

### **5.6.1 Test Limit**

The In-Service Monitoring shall be used to monitor each Operating Channel.

The In-Service-Monitoring shall start immediately after the RLAN has started transmissions on a channel.

During the In-Service Monitoring, the device shall be capable of detecting any of the radar signals that fall within the range given by tables 2-3 and 2-4 with a level above the Interference Detection Threshold defined in table 2-2.

The minimum required detection probability associated with a given radar test signal is defined in table 2-4.

### **5.6.2 Test Procedure Used**

- a) The signal generator and UUT are connected using the test set-up described in clause 2.4.
- b) The UUT shall transmit a test transmission sequence on the selected channel  $Ch_r$ . While the testing is performed on  $Ch_r$ .
- c) At a certain time  $T_0$ , a single burst radar test signal is generated on  $Ch_r$  using radar test signal #1 defined in 2-3 and at a level defined in table 2-2.  $T_1$  denotes the end of the radar burst.
- d) It shall be recorded if the radar test signal was detected.
- e) the Steps c) to d) shall be repeated at least 20 times in the case of test signals simulating fixed frequency radars or 30 times in the case of test signals simulating frequency hopping radars in order to determine the detection probability for the selected radar test signal. The detection probability shall be compared with the limit specified in either table 2-3 or 2-4 as appropriate;
- f) the Steps b) to e) shall be repeated for each of the radar test signals defined in table 2-3 and for each of the radar test signals 1 and 2 in table D 3.2 where the single-burst radar signal is replaced by the multi-burst sequence defined in clause 5.3.6.1.1.

### 5.6.3 Test Result

802.11n-HT20 channel 149 5745MHz

| Radar Wave Type | Detection Threshold | Trail Number | Detection Result | Limit | Note |
|-----------------|---------------------|--------------|------------------|-------|------|
| Type 1          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 2          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 3          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 4          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 5          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Type 6          | -69dBm              | 20           | 100%             | 60%   | Pass |
| Hopping Type 1  | -69dBm              | 20           | 100%             | 60%   | Pass |
| Hopping Type 2  | -69dBm              | 20           | 100%             | 60%   | Pass |


## 5.7. Channel Shutdown and Non-Occupancy Period

### 5.7.1 Test Limit

| Parameter                         | Value    |
|-----------------------------------|----------|
| Channel Move Time                 | < 10 s   |
| Channel Closing Transmission Time | < 260 ms |

### 5.7.2 Test Procedure Used



- The signal generator and UUT are connected using the test set-up described in clause 2.4.
- The UUT shall transmit a test transmission sequence on the selected channel  $Ch_r$ .
- At a certain time  $T_0$ , a single burst test signal is generated on  $Ch_r$  using radar test signal #1 defined in table 2-3 and at a level of up to 10 dB above the level defined in table 2-2 on the selected channel.  $T_1$  denotes the end of the radar burst.
- The transmissions of the UUT following instant  $T_1$  on the selected channel  $Ch_r$  shall be observed for a period greater than or equal to the Channel Move Time defined in table 2-1. The aggregate duration (Channel Closing Transmission Time) of all transmissions from the UUT on  $Ch_r$  during the Channel Move Time shall be compared to the limit defined in 2-1.
- $T_2$  denotes the instant when the UUT has ceased all transmissions on the channel  $Ch_r$ . The time difference between  $T_1$  and  $T_2$  shall be measured. This value (Channel Move Time) shall be noted and compared with the limit defined in table 2-1.
- Following instant  $T_2$ , the selected channel  $Ch_r$  shall be observed for a period equal to the Non-Occupancy Period ( $T_3 - T_2$ ) to verify that the UUT does not resume any transmissions on this channel.



### 5.7.3 Test Result

#### Channel Closing Transmission Time and Channel Move Time


802.11n-HT20 channel 149 5745MHz



| Test Item                         | Measured Time (s) | Limit    | Results |
|-----------------------------------|-------------------|----------|---------|
| Channel Move Time                 | 0.945             | < 10 s   | Pass    |
| Channel Closing Transmission Time | 0.020             | < 0.26 s | Pass    |

## Non-Occupancy Period

### 802.11n-HT20 channel 149 5745MHz



| Test Item            | Measured Time (ks) | Limit    | Results |
|----------------------|--------------------|----------|---------|
| Non-Occupancy Period | > 30 Min           | > 30 Min | Pass    |

The End